



4835 Hollywood Boulevard Suite 4, Hollywood, FL 33021 - P: +1 305-709-7256

# CG-21-32

## Polyalkylene Glycol (PAG) Compressor Oil ISO 32

CG-21-32 offers full compatibility with most OEM polyalkylene glycol (PAG) compressor lubricants. This compatibility means that flushing of the existing compressor oil is not necessary to change to CG-21-32, reducing maintenance costs and downtime. CG-21-32 offers superb resistance against water contamination and an extended service life of 10,000 hours.

### ATTRIBUTES

- 10,000-hour oil life at 100°C discharge temperature
- Compatible with most OEM PAG compressor lubricants
- Resists water contamination
- Protects against wear, rust and corrosion
- Non-toxic/non-hazardous

### TYPICAL LUBRICANT PROPERTIES

<b>CG-21-32 Grades</b>	<b>32</b>	<b>46</b>	<b>68</b>
Viscosity cSt @ 40°C	32	46.1	67
Viscosity cSt @ 100°C	5.4	6.7	8.7
Flash Point °F (°C)	435 (224)	450 (232)	478 (248)
Copper Corrosion	1a	1a	1a
Rust Test: Distilled Water	Pass	Pass	Pass
Rust Test: Salt Water	Pass	Pass	Pass
Foam Sequence I, II, III	0/0/0	0/0/0	0/0/0